

# Sparkle Clean MU10-8

## Hollow Fibre Ultra-Filtration Membrane

### System Includes:

- U860 membrane cartridge (10 cartridges)
- Feed and Backflush Pumps
- 2 control valves
- Feed, Air and Backflush Pressure Gauges
- Product Flow Meter
- Air-scouring Blower
- Stainless or Galvanised Steel Frame
- PVC Piping, Hoses and Quick couplings
- Electrical Control Panel with PLC

Optional Supply: Demo Tank (Transparent)

### System & Operating Specifications:

<b>Configuration</b>	Hollow Fibre
<b>Operation Process</b>	Dead-end filtration ( Out to In ) Air scouring with backflush (In to Out )
<b>Recovery</b>	90 ~ 95 %*
<b>Operating Temperature</b>	< 50° C
<b>Operating Pressure (TMP)</b>	< 8 psi (Feed) <14 psi (Backflush)
<b>Flow Rate (Per membrane)</b> <b>City Water</b> <b>River/ Bore</b> <b>Treated Wastewater</b>	4.0 m <sup>3</sup> /h (56gfd)* 2.5 m <sup>3</sup> /h (35gfd)* 1.5 m <sup>3</sup> /h (21gfd)*
<b>Product Turbidity</b>	< 0.1 NTU *
<b>Electrical Power</b>	400V; 50Hz; 9A; Three Phase
<b>Dimensions (Meter)</b>	3.0 (L) x 1.2 (W) x 2.2 (H)
<b>Weight</b>	700 kg

\* Subject to feed water condition

### Sparkle Clean Tech Pvt. Ltd.

89, Gautam Complex  
Sector-11, CBD Belapur  
Navi Mumbai 400 614, India

Office: +91 (22) 4061-9000

Fax: +91 (22) 2756-3061

E-mail: [sumeetm@acuityemail.com](mailto:sumeetm@acuityemail.com)

